



Scanflood 1 AS

Die-cast body general projector, which is suitable to illuminate the buildings, front sides, and publicity screens and also yards and sport fields. Asymmetric and symmetric light distribution.



Applications

- Front sides, industrial areas, sport fields, publicity screens, parking places and pointing out lightings.

Construction

- Body die-cast, polyester powder painted aluminium
- Heat resistant safety glass 4 mm, quick clips aluminium
- Reflector hammered anodised aluminium
- Tightness is secured with weather proof silicon sealing

Colour

- Dark grey

Installation

- Installation height 5-8 m
- Wholes of attachment handle 3 pcs 10 mm, distribution 55 mm
- Available separate steel pole for up to 5 projectors

Connection

- Terminal block 3 x 2,5 mm²
- 2 pcs PK 11 tube tighter

Light sources

- Metal halide lamp HIT 70 and 150 W , Rx7s

Additional information

- 230 V 50 Hz
- IP65
- -o- 3 x 2,5 mm²
- Measurements: width 275, height 295, depth 155 mm

Product	EAN	Airam nr	Light source W	Cap	Weight kg
ScanFlood 1 AS 70 W	6435200133700	4507237	HIT/HST 70 W	RX7s	4,5
ScanFlood 1 AS 150 W	6435200133717	4507238	HIT/HST 150 W	RX7s	5,2
Scanflood 1 S 70 W	6435200133151	4507252	HIT/HST 70 W	RX7s	4,5
Scanflood 1 S 150 W	6435200133168	4507253	HIT/HST 150 W	RX7s	5,2